DADOO


TECHNICAL CHARACTERISTICS

MODELS

Protection rating (IP) Power supply (V) Power (W)

Operating temperature (°C) Item

DIMENSIONS (MM)



DD-1KA


ADO - FIVIIVIA




54 120 - 230 AC 50/60 Hz - 24 AC - DC 7 (230 V AC) - 4 (120 V AC) - 6 (24 V AC) - 5 (24 V DC) -20 to +55

ABS - PMMA

230 V AC 24 V AC DC







KIARO

TECHNICAL CHARACTERISTICS

MODELS	KLED	KLED24
Protection rating (IP)	54	54
Power supply (V)	120 - 230 AC 50/60 Hz	24 V AC - DC
Power (W)	2 (230 V AC) 1 (120 V AC)	2
Operating temperature (°C)	-20 to +55	-20 to +55
Item	ABS - POLYCARBONATE	ABS - POLYCARBONATE

230 V AC 24 V AC DC

DIMENSIONS (MM)







CE

© KADENBPE18 - 2018 - EN CAME RESERVES THE RIGHT TO MAKE ANY CHANGESTO THIS DOCUMENT, AT ANY TIME. EVEN PARTIAL REPRODUCTION IS PROHIBITED.



CAME S.p.A. has the following Quality, Environmental and Safety certifications: UNI EN ISO 9001 UNI EN ISO 14001 BS OHSAS 18001





CAME S.p.A.

Via Martiri della Libertà, 15 31030 Dosson di Casier Treviso - ITALY

CAME.COM





DADOO / KIARO

FLASHING LIGHTS FOR OPERATOR SYSTEMS.

230 V AC - 120 V AC 24 V AC - DC






CAME.COM



FLASHING LIGHTS CAME

An operator system cannot be said to be complete without a flashing light that warns when the gate or door is moving, to ensure maximum safety for users. CAME's offer meets all needs in terms of reliability, design, energy savings, and always in compliance with European Regulations.



DADOO


Formal elegance and technological innovation

With its innovative and particular design this flashing light features LED lighting technology for longer life and lower consumption. Compared to more traditional light bulbs, LED technology is longer lasting and cuts energy consumption to only 6 Watts. They can be wallmounted thanks to a handy standard support. All of the models work with different voltage values: 230 V AC, 120 V AC, 24 V AC - DC.

FINISH AND LIGHTS

MODELS	DD-1KA	DD-1KB
LIGHT COLOUR	Amber	Blue
SUPPORT COLOUR	Charcoal	Charcoal

The Dadoo series lets you custom-choose the LED light color for your entry point. The available models are in charcoal grey with either amber or blue light.



KEY FEATURES OF DADOO,

- Long life and low consumption.
- DADOO is the only universal LED flashing-light because it works with different power-supply voltages: 230 V AC - 120 V AC - 24 V AC - DC.
- DADOO is set up to fit different types of antenna either on the left or right.



KIARO

Low consumption movement warning flashing-light

Flashing light featuring sleek design made with high-quality materials. They come in two models, both with LED-technology lighting that makes them especially efficient, one with voltage at 230 V AC, and one at 24 V AC-DC. They can be wall-mounted thanks to a handy support (optional).

KIARO KEY FEATURES

- Sleek design and materials of the highest qualityfor a flashing light that offers much more than a simple luminous warning device.
- Long life and very low consumption.
- Energy efficiency is linked to lower consumption (1W - 120 V AC / 2W - 230 V AC / 2W - 24 V AC - DC).
- The wall-mounting support completes the availability of mounting accessories.
- KIARO is set up to fit different types of antenna either on the left or right.



READ UP AT CAME.COM ABOUT THE FULL RANGE OF CAME OPERATORS AND ACCESSORIES



TRANSMITTERS

PHOTOCELLS SELECTORS KEY-OPERATED SELECTORS WITH KEYPAD

CAME is a market leading home, industrial, and special technological projects automation manufacturing company. A full range of household solutions: from operators for gates and garage doors, to shutter and awning winding motors, and even home automation control, to burglar proof and video entry systems. Technology and reliability to serve your business, thanks to solutions designed for powering large industrial doors, automatic doors, street barriers, turnstiles, access control systems and parking facilities.

CAME.COM